

Ensure a reliable connection

with this S-Video cable

Depend on this cable to provide you with a reliable video connection between components.

Enjoy better picture quality

- Signal degradation is minimized with gold plated connectors
- Protects against signal loss

• Bare copper shielding

Easy installation

• Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket



Specifications

Inner Carton

- Gross weight: .36 kg
 Inner carton (L x W x H): 24.3 x 15.6 x 10.5 cm
- Nett weight: .16 kg
- Tare weight: .2 kg

Outer Carton

- Gross weight: 2.8 kg
 Outer carton (L x W x H): 34 x 27.5 x 30.5 cm
- Nett weight: .96 kg
- Tare weight: 1.84 kg
- **Packaging dimensions**
- Packaging dimensions (W x H x D): 9.5 x 23.5 x 3.7 cm
- Gross weight: .06 kg
- Nett weight: .04 kg
- Tare weight: .02 kg

SWV7511W/10

Highlights

Gold plated connectors

High quality connectors which minimize signal loss.

Bare copper shielding Bare copper shielding protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.



Issue date 2009-04-11

© 2009 Koninklijke Philips Electronics N.V. All Rights reserved.

Version: 1.0.6

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

12 NC: 8670 000 39421 EAN: 87 12581 41756 7

www.philips.com